



Dart Aerospace Ltd.
1270 Aberdeen St
Hawkesbury, ON
K6A 1K7
Canada

Tel (613) 632-5200

D350-748-201
Job Sheet 174651



Part No: D350-748-201

Job Qty: 1 ea

Part Name: Aft Crosstube AS350 / AS355



Part Weight: 0 lbs

Status: Scheduled

Priority: Medium

Job Created: 3/20/18

Job Tracking No:

Due Date: 7/20/18

Created By: Marie Lajeunesse

Type: SOLD

Description:

Note: DWG REV H IPP Rev: A New Issue 06-07-05 JLM IPP Rev: B Update qty of MS21042L5 06-09-12 KJ IPP Rev C Combined manufacturing 08.04.02 EC verified: DD IPP Rev: D 08-06-24 revD as per dwg DD verified: EC IPP Rev: E 08.12.11 Step17 was step 21 KJ Verified: EC IPP Rev: F 10.08.04 added QSI010 4.3 DD ver: EC IPP Rev: G ADD UNDER BEND COMMENT 12-05-28 JLM IPP REV: H 12.11.05 as per dwg D350-748-141G DD ver: JLM IPP REV: I 15.03.19 as per dwg D350-748-241 revH dd ver: jlm

Ship Via:

Bill of Materials

Job Routing

Op No	Operation	Qty	Start Date	Due Date	Standard		Workcenter/Supplier		Sign-off
					Setup hrs	Run Hrs	Workcenter / Supplier	Lead Time	
90	Start up Operation	1 Ea	7/19/18	7/19/18	0.00	0.00	Start Up Crosstubes-1		GP 18-07-20
110	CNC Bend Crosstubes	1 pcs	7/19/18	7/19/18	0.00	2.94	CNC Bend Crosstube		GP 18-07-20
120	Crosstubes	1 pcs	7/19/18	7/19/18	0.00	2.65	Crosstubes-2		GP 18-07-20
125	Outsource	1 pcs	7/19/18	7/19/18	0.00	0.00	Outsource1		CT 18-7-20
126	Packaging	1 pcs	7/19/18	7/19/18	0.00	0.00	Packaging2		md 18-07-24
127	QC	1 pcs	7/19/18	7/19/18	0.00	0.00	QC15		
128	Crosstubes	1 pcs	7/19/18	7/19/18	0.00	2.65	Crosstubes-2		
130	Crosstubes	1 pcs	7/19/18	7/19/18	0.00	1.85	Crosstubes-2		
140	QC	1 pcs	7/19/18	7/19/18	0.00	0.00	QC6		
150	Outsource	1 pcs	7/19/18	7/19/18	0.00	0.00	Outsource3		
160	Packaging	1 pcs	7/19/18	7/19/18	0.00	0.00	Packaging2		
170	QC	1 pcs	7/19/18	7/19/18	0.00	0.00	QC6		
174	Outsource	1 pcs	7/19/18	7/19/18	0.00	0.00	Outsource2		
176	Packaging	1 pcs	7/19/18	7/19/18	0.00	0.00	Packaging2		
178	QC	1 pcs	7/19/18	7/19/18	0.00	0.00	QC5		
180	SprayPaint	1 pcs	7/19/18	7/19/18	0.00	0.88	Spray Paint		
190	QC	1 pcs	7/19/18	7/19/18	0.00	0.00	QC14		
200	Crosstubes	1 pcs	7/20/18	7/20/18	0.00	1.85	Crosstubes-2		
210	QC	1 pcs	7/20/18	7/20/18	0.00	0.00	QC5		
220	Packaging	1 pcs	7/20/18	7/20/18	0.00	0.00	Packaging1-3		
230	QC	1 pcs	7/20/18	7/20/18	0.00	0.00	QC4		
235	DC	1 pcs	7/20/18	7/20/18	0.00	0.00	DC		
240	Packaging	1 pcs	7/20/18	7/20/18	0.00	0.00	Packaging3-1		
250	QC21-FG	1 Ea	7/20/18	7/20/18	0.00	0.00	QC21		

Part Op 110 - Bend tube as per Dwg D350-748-241 using CNC bender program D350A and Folio FT *****UNDER

Descriptions: BEND .225" PER SIDE*****

120 - ****VERIFY CROSSTUBE DIMENSIONS AS PER DWG****

125 - ISSUE P/O TO METCOR: 20040561

127 - ***MARK CUT LINES***

128 - CUT TUBE AT HEIGHT ON FAI SHEET

130 - 2- Drill Tube as per Dwg D350-748-241 Using DT8876 Drill Jigs, 3 -Deburr 4- Engrave Part # and Batch # as per

DQA: _____ Date: _____

WORK ORDER NON-CONFORMANCE / UPDATE



QA Closed: _____ Date: _____

Work Order update only ☐

Work Order: _____		DISPOSITION		AGAINST DEPARTMENT/PROCESS						
Part No. _____		Rework ☐		Skid-tube ☐	Cross tube ☐	Water Jet ☐	Engineering ☐			
NCR No. _____		Scrap ☐		Machining ☐	Small Fab ☐	Prod. Eng. Coord. ☐	Quality ☐			
		Use-as-is ☐		Thermoforming ☐	Finishing ☐	Rec/Store/Packaging ☐	Other ☐			
		Suspected Unapproved ☐		Large Fab ☐	Composite ☐	Supplier ☐				
Date : _____		Step # : _____		QTY Effective : _____			MRB (QSI042) Approval			
Description Work Order Deviation				Disposition				Completed By		
 1270 Aberdeen Street Hamilton, ON K8A 1K7 CANADA TEL: 1 613 632-5200 Email: sales@dartaero.com www.dartaero.com Container No: S094600 Part: D350-748-201 Job No: 174651 Serial No/Batch: S094600 Revision: Inspector: Exp Date: Instructions: Date: 07/20/18								Lead hand / Supervisor Approval Verification		
								QC / QA Coordinator Approval		
Root Cause										
Environment ☐	☐	No Re-verification ☐						Positioned Wrong ☐		
Design ☐	☐	Operator ☐						Outside Dimensions ☐		
Doc/Data ☐	☐	Offset/Setup ☐						Over/Under tolerance ☐		
Equip/Tooling ☐	☐	Supplier ☐						Part Incorrect ☐		
Handling/Pre ☐	☐	Training ☐						Part Lost/Missing ☐		
Material ☐	☐	Use for Testing ☐						Part Moved ☐		
Internal Transport ☐	☐	Poor Information ☐		Crushing ☐				Drawing ☐		
Tribal Knowledge ☐	☐	Rushing ☐		Heat Treat ☐		Cut Too Short ☐		Finish ☐		
LOA ☐	☐	Product Improvement ☐		Wave/Twist in Tube ☐		Instructions Incomplete/Unclear ☐	Fit/Function ☐	Misread ☐		
Substation ☐	☐	Process Improvement ☐		Marks/Chatter ☐		Drill Holes ☐	Misaligned/off center ☐	Turning Sequence ☐		
Past Expiry Date ☐	☐	Manufacturing Process ☐								
Misidentified ☐	☐	Past Due ☐		OTHER : _____						

Dwg D350-748-241 5-Remove all marks from tube within limits of D350-748-241

150 - Issue P/O: _____

160 - Ensure certificate of conformity is attached

174 - ISSUE P/O TO ACCUREN: _____

180 - 1-Prime inside and out crosstube as per QSI 005 4.2

190 - Then,Wrap in plastic bag to protect from scratches

200 - INSTALL GROUND WIRE INSERT, THEN INSERT SCREW AND WASHER 2-Install supports with Proseal 890 per D350-748-241 and QSI 015 EXP: _____ 3-Install supports clamps Using Dt8876 as per Dwg D350-748-241,Torque to 60-80 IN-LBS.

235 - Photocopy bluefile & type labels per PPPD350-748-201 CHG003

240 - Identify and pack for shipping as per PPPD350-748-201 PPP Rev: _____

Job BOM

Part / Item	Component Name	Quantity	Operation	Container
D350-748-241TRN	Crosstube Turning Detail	1 (1 ea)	90-Start up Operation	
ALS4-1032-225	Rivnut	1 Ea (1 ea)	200-Crosstubes	
D3502-1	Support	2 Ea (2 ea)	200-Crosstubes	
D5123-7	Clamp Cushion	2 Ea (2 ea)	200-Crosstubes	
MS21920-20	Clamp	2 Ea (2 ea)	200-Crosstubes	
MS27039-1-10	Screw	1 Ea (1 ea)	200-Crosstubes	
NAS1149D0363J	Washer	1 Ea (1 ea)	200-Crosstubes	
AN4-41A	Bolt	8 Ea (8 ea)	220-Packaging	
AN4-6A	Bolt	16 Ea (16 ea)	220-Packaging	
AN5-32A	Bolt	4 Ea (4 ea)	220-Packaging	
D3500-1	Saddle	4 Ea (4 ea)	220-Packaging	
D3501-1	Bushing	16 Ea (16 ea)	220-Packaging	
MS21042L4	Nut	24 Ea (24 ea)	220-Packaging	
MS21042L5	Nut	4 Ea (4 ea)	220-Packaging	
NAS1149D0463J	Washer	32 Ea (32 ea)	220-Packaging	
NAS1149D0563J	Washer	8 Ea (8 ea)	220-Packaging	

Job Allocations

Operation	Component Part	Required	Inventory	Allocated
90-Start up Operation	D350-748-241TRN	1	0	0
200-Crosstubes	ALS4-1032-225	1	1,149	0
	D3502-1	2	62	0
	D5123-7	2	145	0
	MS21920-20	2	108	0
	MS27039-1-10	1	313	0
	NAS1149D0363J	1	3,131	0
220-Packaging	AN4-41A	8	230	0
	AN4-6A	16	620	0
	AN5-32A	4	114	0
	D3500-1	4	101	0
	D3501-1	16	99	0
	MS21042L4	24	2,466	0
	MS21042L5	4	722	0
	NAS1149D0463J	32	3,386	0
	NAS1149D0563J	8	2,107	0

Part Specifications

Specifications could not be found.

DQA: _____ Date: _____



WORK ORDER NON-CONFORMANCE / UPDATE

QA Closed: _____ Date: _____

Work Order update only ☐

Work Order: <u>174651</u>	DISPOSITION Rework ☐ Scrap ☒ Use-as-is ☐ Suspected Unapproved ☐	AGAINST DEPARTMENT/PROCESS			
Part No. <u>D350-748-201</u>		Skid-tube ☐	Cross tube ☒	Water Jet ☐	Engineering ☐
NCR No.		Machining ☐	Small Fab ☐	Prod. Eng. Coord. ☐	Quality ☐
		Thermoforming ☐	Finishing ☐	Rec/Store/Packaging ☐	Other ☐
		Large Fab ☐	Composite ☐	Supplier ☐	


Date: 18-08-15 Step #: 127 QTY Effective: ① MRB (QSI042) Approval

Description Work Order Deviation	Disposition	MRB (QSI042) Approval
$\frac{1}{2}$ span is under tolerance. Min tolerance is 40.77 and actual measurement is 40.375	Scrap destroy.	<u>18-08-15</u> Completed By Lead hand / Supervisor Approval Verification DAS 9 9-89 <u>18-08-15</u> QC / QA Coordinator Approval DAS 9 9-89 <u>18-08-15</u>

Root Cause				FAULT CATEGORY			
Environment ☐	No Re-verification ☐	Pressure/Forced ☐	Temperature/Cure ☐	Power Loss/Surge ☐	Positioned Wrong ☐		
Design ☐	Operator ☒	Bending ☐	Set-up ☐	Folio/Program ☐	Outside Dimensions ☐		
Doc/Data ☐	Offset/Setup ☐	Centre Not Concentric ☐	BOM/Route ☐	Grain ☐	Over/Under tolerance ☐		
Equip/Tooling ☐	Supplier ☐	Cracks ☐	Broken/Damage/Defect ☐	Weld ☐	Part Incorrect ☐		
Handling/Pre ☐	Training ☐	Crimp/Kink/Ripple/Wave ☐	Inspection Incomplete/Unqualified ☐	Wrong Stock Pulled ☐	Part Lost/Missing ☐		
Material ☒	Use for Testing ☐	Cuffs ☐	Contamination ☐	Out of Sequence ☐	Part Moved ☐		
Internal Transport ☐	Poor Information ☐	Crushing ☐	Countersink ☐	Off-set ☐	Drawing ☐		
Tribal Knowledge ☐	Rushing ☐	Heat Treat ☐	Cut Too Short ☐	Mislabeled ☐	Finish ☐		
LOA ☐	Product Improvement ☐	Wave/Twist in Tube ☐	Instructions Incomplete/Unclear ☐	Fit/Function ☐	Misread ☐		
Substation ☐	Process Improvement ☐	Marks/Chatter ☐	Drill Holes ☐	Misaligned/off center ☐	Turning Sequence ☐		
Past Expiry Date ☐	Manufacturing Process ☐	OTHER: _____					
Misidentified ☐	Past Due ☐						

DART AEROSPACE LTD	Work Order:	174651
Description: Crosstube High Aft (AS350/355)	Part Number:	D350-748-201
Inspection Dwg: D350-748-241 Rev: H		Page 1 of 1

Required Dimension	Min	Max
Height	31.10	31.60
1/2 Span	40.77	41.03
Angle	75	77
Total Span	81.54	82.06
Bending Passes	7	--
Crushing	--	8%
Twist	--	0.38



	Side A	Side B
Bending Passes	35	35
Crushing	4.7%	5%
Comments		

QC15 Inspection	
Date	

Rev	Date	Change	Revised by	Approved
A	07.02.06	New Issue	KJ/JM	
B	10.08.23	Dwg Rev updated	KJ	
C	12.04.16	Added bending, crushing & twist dimensions	KJ	
D	12.07.31	Dwg Rev updated	KJ	
E	13.02.27	Dwg Rev updated	KJ	
F	14.02.13	Crushing & twist dimensions revised	KJ	
G	14.11.10	Height dimension revised	KJ	
H	15.07.20	Crushing dimension revised	KJ	

Item	Qty -241	Part Number	Description
1	X	D350-748-241	CROSSTUBE ASSEMBLY (AS 350/355 HI AFT)
2	1	D6015-125	CROSSTUBE (OR D6018-125)
3	2	D3502-1	SUPPORT
4	2	D5123-7	CLAMP CUSHION
5	1	AELS-1032-225	INSERT
6	1	NAS1149D0363J	WASHER (OR AN960JD10)
7	2	MS21920-20	CLAMP (OR MS21920-21/-22, PER DART SPEC. M-MS21920-21/-22)
8	1	MS27039-1-10	SCREW
9	A/R	PROSEAL 890 B-2	SEALANT, AMS-S-8802 CLASS B-2

GENERAL NOTES:

- 1) MATERIAL: MANUFACTURED FROM D6015-125 OR D6018-125
FINISHED LENGTH AFTER TURNING = 124.70±0.06 (AFTER BENDING/TRIMMING = 122.70 REF)
- 2) FINISH: MAGNETIC PARTICLE INSPECT PER DART QSI 038 4.2
CADMIUM PLATE PER AMS-QQ-P-416B, CLASS 1, TYPE II
PRIME INSIDE AND OUTSIDE PER DART QSI 005 4.2
PAINT OUTSIDE PER DART QSI 005 4.2
- 3) TOLERANCE: PER DART QSI 018 UNLESS OTHERWISE NOTED.
WALL THICKNESS ECCENTRICITY PER DART QSI 038 7.2
MIN. ALLOWABLE WALL IS -0.020 FROM NOMINAL
- 4) UNITS: INCHES UNLESS OTHERWISE NOTED.
- 5) BREAK SHARP EDGES: 0.005 TO 0.010 MAX.
- 6) IDENTIFICATION: DART PART NUMBER "D350-748-241" AND BATCH NUMBER ON INSIDE OF CUFF
PER DART QSI 044 6.4 (VIBRATING STYLUS)
- 7) WEIGHT: 29.85 lbs
- 8) PART IS SYMMETRIC ABOUT CENTERLINE, EXCEPT FOR Ø0.297 HOLE.
- 9) EXTREME CARE MUST BE TAKEN TO PROTECT THE OUTSIDE SURFACE OF THE TUBE. THE OUTSIDE SURFACE MUST BE SMOOTH AND FREE FROM SURFACE DEFECTS SUCH AS SCRATCHES, NICKS, OR DENTS. DEFECTS UP TO 0.005" MAY BE BLENDED OUT LONGITUDINALLY. CIRCUMFERENTIAL GRIND MARKS ARE UNACCEPTABLE. WHEN DRILLING HOLES EXTREME CARE MUST BE TAKEN AND CAREFUL DEBURRING PERFORMED TO ENSURE A CLEAN HOLE WITH NO CRACKING/CHIPPING/GROOVES.

TURNING

- 10) BLEND OUT ALL EDGES FROM MACHINING LONGITUDINALLY, TRANSITION SHOULD BE SMOOTH. NOTE: ALL HOLES ARE DRILLED AFTER BENDING.
- 11) HEAT TREAT TO MIN. 180 KSI PER MIL-T-6736 OR AMS2759/1E AFTER TURNING. ACCEPTABLE TO VERIFY TENSILE STRENGTH BY HARDNESS TEST PER ASTM E18 TO 40-45 HRC.

BENDING

- 12) ALL DIMENSIONS FOR BENT TUBE ARE POST STRESS RELIEF
- 13) BEND PROGRESSIVELY WITH A MINIMUM OF 7 PASSES PER SIDE. MAXIMUM TUBE FLATTENING DUE TO BENDING IS 6% BASED ON O.D. ON TOP HALF OF BEND, AND 8% ON BOTTOM HALF OF BEND.
- 14) MAX AMPLITUDE OF RIPPING ALONG BENT PORTION OF THE TUBE IS 0.030 (ZN A1-3)
- 15) AFTER BENDING, STRESS RELIEVE TUBE AT 650°F ±10.25°F FOR A MINIMUM OF 2 HRS AND ALLOW TO COOL TO AMBIENT TEMPERATURE (REF AMS2759/1E).
- 16) MAX TWIST AFTER STRESS RELIEF: WITH XTUBE LAYED FLAT ON SURFACE, THE DIFFERENCE BETWEEN CUFF HEIGHTS FROM THE SURFACE MAY BE NO LARGER THAN 0.38 (ZN C1-3).

ASSEMBLY

- 17) TO INSTALL D3502-1 SUPPORT: ABRASE MATING SURFACE OF SUPPORT AND CROSSTUBE WITH 180-GRIT SANDPAPER AND REMOVE RESIDUE WITH MEK (OR EQUIVALENT). APPLY A 0.02" TO 0.05" THICK LAYER OF PROSEAL 890 CLASS B-2 (OR AMS-S-8802 CLASS B-2) SEALANT TO MATING SURFACE OF SUPPORT.
- 18) TORQUE CLAMPS 60 TO 80 IN-LB. ENSURE AT LEAST 1.5 THREADS SHOWING IN SAFETY AND THAT NUT HAS NOT BOTTOMED-OUT AFTER TORQUING. PRIOR TO PACKAGING, RE-CHECK TORQUE ON CLAMPS AFTER PROSEAL 890 SEALANT HAS CURED FOR 72 HOURS.

SHOP COPY
RETURN TO
ENGINEERING
UNCONTROLLED COPY
SUBJECT TO AMENDMENT
WITHOUT NOTICE
WORK ORDER
NO. 174654 MJS
1803-21

RELEASED


2015 MAR 18

4P ECH 15-547

H	D5123-7 WAS D3595-063-395, MS21920-20 WAS -22, ALLOWABLE CRUSHING NOW 8% WAS 7%, 14.00 WAS 14.37 (D5-2), 12.32 WAS 12.89 (D5-3)	CP	15.02.25
G	RMV ABRASION STRIP, SUPPORT NOW W/ PROSEAL & CUSHION, ADD STRESS RELIEF, LONGER CUFF, NOW TRIM'D AFTER BEND, ADD WALL DIMS & UPDATE TOL.	CP	12.09.12
F	ADD HRC TEST OPTION (B8-1) PER PAR 09-040, ADD TWIST LIMIT (A8-1, C1-3), ADD D6015-125 OPTION (C8-1), STOCK DIM NOW MACHINED (D1-4)	CP	10.11.23
E	REVISE GENERAL NOTES; UPDATE TO CURRENT STANDARDS; RELOCATED FLAG #6 PER PAR 08-046 (ZN A8-3); ADD TOLERANCES (ZN C6-3, D2-3)	RF	09.09.30
D	MAG. PARTICLE AND CAD PLATE AS MFD.	CP	08.10.31
C	ADD CAD PLATING	CP	06.08.14
B	ADD D6018-125 & PRIME AND PAINT	CP	06.06.30
A	NEW ISSUE	CP	06.03.31
REV.	DESCRIPTION	BY	DATE
DESIGN	9P	DART AEROSPACE LTD HAWKESBURY, ONTARIO, CANADA	
DRAWN	9P		
CHECKED	ALS	DRAWING NO.	REV. H
MFG. APPR.	15	D350-748-241	SHEET 1 OF 4
APPROVED	15	TITLE	SCALE
DE APPR.	15	CROSSTUBE (AS 350/355 HI AFT)	NTS
DATE	15.02.25	COPYRIGHT © 2006 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSES OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	

1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900

**D350-748-241
ASSEMBLY DETAIL**



SECTION A-A D4-2
SCALE 6X

INSTALL THIS SIDE ONLY, AFTER FINISH:
AELS-1032-225 INSERT
NAS1149D0363J WASHER
MS27039-1-10 SCREW


17 18
D3502-1 SUPPORT
MS21920-20 CLAMP (OR -21/-22)
D5123-7 CLAMP CUSHION
2 PL


D350-748-241
BENT TUBE

RELEASED

2015 MAR 18


DESIGN		DART AEROSPACE LTD	
DRAWN		HAWKESBURY, ONTARIO, CANADA	
CHECKED	ALS	DRAWING NO.	REV. H
MFG. APPR.		D350-748-241	SHEET 2 OF 4
APPROVED		TITLE	SCALE
DE APPR.		CROSSTUBE (AS 350/355 HI AFT)	NTS
DATE	15.02.25	COPYRIGHT © 2006 BY DART AEROSPACE LTD THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT WRITTEN PERMISSION FROM DART AEROSPACE LTD.	





DART AEROSPACE LTD	Work Order:	
Description: Crosstube High Aft (AS350/355)	Part Number:	D350-748-201
Inspection Dwg: D350-748-241 Rev: H		Page 1 of 1

Required Dimension	Min	Max
Height	31.10	31.60
1/2 Span	40.77	41.03
Angle	75	77
Total Span	81.54	82.06
Bending Passes	7	--
Crushing	--	8%
Twist	--	0.38



	Side A	Side B
Bending Passes	35	35
Crushing		
Comments		

QC15 Inspection	
Date	

Rev	Date	Change	Revised by	Approved
A	07.02.06	New Issue	KJ/JM	
B	10.08.23	Dwg Rev updated	KJ	
C	12.04.16	Added bending, crushing & twist dimensions	KJ	
D	12.07.31	Dwg Rev updated	KJ	
E	13.02.27	Dwg Rev updated	KJ	
F	14.02.13	Crushing & twist dimensions revised	KJ	
G	14.11.10	Height dimension revised	KJ	
H	15.07.20	Crushing dimension revised	KJ	

[Handwritten signatures]

539



Dart Aerospace Ltd.
1270 Aberdeen St
Hawkesbury, ON
K6A 1K7
Canada

Tel (613) 632-5200

PURCHASE ORDER **PO040561**

Supplier: MEI001-VC
Metcor Inc.
560 Boul. Arthur Sauve
Saint-Eustache
QC
J7R 5A8 Canada
Phone: 450 473 1884
Fax: 450 491 5498

PO No: PO040561
PO Date: 7/20/18
Due Date: 7/27/18
Purchase Order
Revision:
Revision Date:
Ship-To Contact: Phone:

Ship To: 1270 Aberdeen Street
Hawkesbury
ON
K6A 1K7 Canada
Phone: 613-632-5200

Via: Ground
Pymt Terms: Net 30
Freight Terms:
Special Comments:

Items

Line Item	Job	Part	Description	Status	Account	Due Date	Order Quantity	Received Quantity	Balance	Unit Price (CAD)	Extended Price
1	174650	D350-748-201	Aft Crosstube AS350 / AS355 : TC STC SH06-27 Issue 2, FAA STC SR02359NY 11/03/04, EASA STC EASA.10016903 Revision 2 10/09/03, BRAZIL 2009S04-04 09/04/06 ISSUE P/O TO METCOR: AFTER BENDING: STRESS RELIEF AT 650° F ± 25° F FOR A MINIMUM OF 2 HRS AIR COOL TO AMBIENT TEMPERATURE note: crosstube made from 4130 seamless steel tube DETAIL C OF C REQUIRED	Firmed	-	7/27/18	1 pcs	0 pcs	1 pcs	\$205.00/pcs	\$205.00
	174651			Firmed	-	7/27/18	1 pcs	0 pcs	1 pcs	\$205.00/pcs	\$205.00
	174676			Firmed	-	7/27/18	1 pcs	0 pcs	1 pcs	\$205.00/pcs	\$205.00
	174674			Firmed	-	7/27/18	1 pcs	0 pcs	1 pcs	\$205.00/pcs	\$205.00
	174673			Firmed	-	7/27/18	1 pcs	0 pcs	1 pcs	\$205.00/pcs	\$205.00
Sub Total:							5	0	5		\$1,025.00

Grand Total: \$1,025.00

Order Notes

Terms & Condition of Purchasing(Suppliers) and Procurement Quality Clauses are an integral part of our AS9100 requirements. To learn in detail, please visit www.dartaerospace.com for further explanation.

Plex 7/20/18 2:42 PM dart.tsimiklis.chrisoula

CT.

METCOR INC.

560 BOUL. ARTHUR-SAUVÉ
ST-EUSTACHE, QC J7R 5A8
Tel: 450-473-1884 / Fax: 450-491-5498

Reçu de livraison

Delivery Receipt

BON DE TRAVAIL Order	EXPÉDITEUR Shipper ID	BON D'EXPÉDITION Shipper
329270	1	129797

EXPÉDITION COMPLÈTE / Shipped Complete

CLIENT /Customer 215

DART AEROSPACE
1270 ABERDEEN
HAWKESBURY, ON K6A 1K7
Ph: 613-632-5200
Fax: 613-632-1053



LIVRÉ À /Shipped To

DART AEROSPACE
1270 ABERDEEN
HAWKESBURY, ON K6A 1K7
Ph: 613-632-5200
Fax: 613-632-1053

COMMANDE DU CLIENT Customer PO	BON DE LIVRAISON DU CLIENT Customer Shipper No.	TYPE DE MATÉRIEL Material Type	DATE DE LA COMMANDE Order Date	TRANSPORTEUR Carrier
40561		Steel	2018/7/20	CLIENT

QUANTITÉ Quantity	No. PIÈCE / Part No.	NOM DE LA PIÈCE / Part Name	DESCRIPTION DE LA PIÈCE Part Description	POIDS Weight
----------------------	-------------------------	--------------------------------	---	-----------------

5 D350-748-201
CROSSTUBE
(5) D350-748-101
JOB 174650,174651,174676,174674,174673,
1 NIL

TYPE DE CONTENEUR Container Type	# DE CONTENEURS # Of Containers	COMMENTAIRES CONTENEUR Container Comments
NIL	1	

CERTIFICAT

EMPAQUETAGE Packing	
------------------------	--

QUANTITÉ EXPÉDIÉE / Quantity Shipped : 5

POIDS EXPÉDIÉ / Weight Shipped : 150,00

QUANTITÉ RESTANTE / Quantity Remaining : 0

POIDS RESTANT / Weight Remaining : 0,00

APPROUVÉ

CERTIFICAT

QUANTITÉ EXPÉDIÉE Quantity Shipped: 5

POIDS EXPÉDIÉ / Weight Shipped : 150,00

Signature:

Date:

METCOR INC.

560 BOUL. ARTHUR-SAUVÉ, ST-EUSTACHE, QC, J7R 5A8

Tél.: 450-473-1884

Télécopieur / Fax administration: 450-491-5498

Télécopieur / Fax production: 450 491-6454

Certificat de Conformité Certificate of Compliance

BON DE TRAVAIL order	CHARGEMENT load
329270	1

CLIENT / customer 215

DART AEROSPACE

1270 ABERDEEN

HAWKESBURY

ON K8A 1K7

LIVRÉ À / shipped to:

DART AEROSPACE

1270 ABERDEEN

HAWKESBURY

ON K8A 1K7

1

COMMANDE DU CLIENT customer po	CLASSIFICATION PIECE part classification	MATÉRIEL material	MAÎTRE D'OEUVRE prime contractor	PROGRAM
40561	N/A	Steel		

SPÉCIFICATIONS DU PROCÉDÉ processing specifications

STRESS REL

SAE AMS 2759/1 REV.E


EXIGENCE / requirement	SPÉCIFICATIONS / specified	TESTS EXÉCUTÉS / performed	RÉSULTATS DE TESTS / results
Visual			

QUANTITÉ quantity	POIDS weight	DESCRIPTION DES PIÈCES parts description
5	150	D350-748-201 CROSSTUBE (5) D350-748-101 JOB 174650,174651,174676,174674,174673, 1 NIL

23/7/18

COMMENTAIRES / comments

APPROUVÉ par / Approved by:



METCOR

DATE: 2018-07-23

APPROUVÉ

METCOR INC.

560 BOUL. ARTHUR-SAUVÉ, ST-EUSTACHE, QC, J7R 5A8

Tél.: 450-473-1884

Télécopieur / Fax administration: 450-491-5498

Télécopieur / Fax production: 450 491-6454

Certificat de Conformité Détaillé

Detailed Certificate of Compliance

BON DE TRAVAIL order	CHARGEMENT load
329270	1

CLIENT / customer 215

DART AEROSPACE

1270 ABERDEEN

HAWKESBURY

ON K6A 1K7

LIVRÉ À / shipped to:

DART AEROSPACE

1270 ABERDEEN

HAWKESBURY

ON K6A 1K7

1

COMMANDE DU CLIENT customer po	CLASSIFICATION PIECE part classification	MATÉRIEL material	MAÎTRE D'OEUVRE prime contractor	PROGRAM
40561	N/A	Steel		
SPÉCIFICATIONS DU PROCÉDÉ processing specifications				
STRESS REL				
SAE AMS 2759/1 REV.E				
EXIGENCE / requirement SPÉCIFICATIONS / specified TESTS EXÉCUTÉS / performed RÉSULTATS DE TESTS / results				
Visual				
QUANTITÉ quantity	POIDS weight	DESCRIPTION DES PIÈCES parts description		
5	150	D350-748-201 CROSSTUBE (5) D350-748-101 JOB 174650,174651,174676,174674,174673, 1 NIL		

COMMENTAIRES / comments

STRESS RELIEF 650F, 2 HRS

Heat treatment (HT) was performed with equipment that meets the requirements of AMS2759 & AMS2750.

All HT operations were in compliance with AMS2759 and all verifications have been performed and documented. No unauthorized changes were performed in regards to the HT. We certify that the material was manufactured, sampled, tested and inspected in accordance with AMS2759 and the purchase order and was found to meet the requirements.

This document and any attached documents may contain confidential or proprietary information and may be subject to export control laws and regulations. If you are not the intended recipient, you are notified that any dissemination, copying of this e-mail and any attachments thereto or use of their contents by any means whatsoever is strictly prohibited. Unauthorized export or re-export is prohibited.

Le traitement thermique (TT) a été fait en utilisant des équipements en conformité avec AMS2759 et AMS 2750.

Le TT a été fait tel que requis par AMS2759 et toutes les vérifications et les tests demandés ont été faites et documentés.

Aucun changement n'a été faite par rapport au TT. On certifie que le matériel a été fabriqué, échantillonné, testé et inspecté en accord avec AMS2759 et le bon de commande et le matériel rencontre les exigences spécifiées.

Ce document et les documents qui lui sont joints peuvent contenir des informations confidentielles, être soumis aux réglementations relatives au contrôle des exportations ou ayant un caractère privé. S'ils ne vous sont pas destinés, nous vous signalons qu'il est strictement interdit de les divulguer, de les reproduire ou d'en utiliser de quelque manière que ce soit le contenu. Toute exportation ou réexportation non autorisée est interdite.

APPROUVÉ par / Approved by:

Isabel Otero
Technician



DATE: 2018-07-23

